




DEPARTMENT OF AIML
Link layer Services & Framing:

Data Link Layer

- In the OSI model, the data link layer is a 4th layer from the top and 2nd layer from the bottom.
- The communication channel that connects the adjacent nodes is known as links, and in order to move the datagram from source to the destination, the datagram must be moved across an individual link.
- The main responsibility of the Data Link Layer is to transfer the datagram across an individual link.
- The Data link layer protocol defines the format of the packet exchanged across the nodes as well as the actions such as Error detection, retransmission, flow control, and random access.
- The Data Link Layer protocols are Ethernet, token ring, FDDI and PPP.
- An important characteristic of a Data Link Layer is that datagram can be handled by different link layer protocols on different links in a path. For example, the datagram is handled by Ethernet on the first link, PPP on the second link.



- **Framing & Link access:** Data Link Layer protocols encapsulate each network frame within a Link layer frame before the transmission across the link. A frame consists of a data field in which network layer datagram is inserted and a number of data fields. It specifies the structure of the frame as well as a channel access protocol by which frame is to be transmitted over the link.
- **Reliable delivery:** Data Link Layer provides a reliable delivery service, i.e., transmits the network layer datagram without any error. A reliable delivery service is accomplished with transmissions and acknowledgements. A data link layer mainly provides the reliable delivery service over the links as they have higher error rates and they can be corrected locally, link at which an error occurs rather than forcing to retransmit the data.
- **Flow control:** A receiving node can receive the frames at a faster rate than it can process the frame. Without flow control, the receiver's buffer can overflow, and frames can get lost. To overcome this problem, the data link layer uses the flow control to prevent the sending node on one side of the link from overwhelming the receiving node on another side of the link.
- **Error detection:** Errors can be introduced by signal attenuation and noise. Data Link Layer protocol provides a mechanism to detect one or more errors. This is achieved by adding error detection bits in the frame and then receiving node can perform an error check.




DEPARTMENT OF AIML

- **Error correction:** Error correction is similar to the Error detection, except that receiving node not only detect the errors but also determine where the errors have occurred in the frame.
- **Half-Duplex & Full-Duplex:** In a Full-Duplex mode, both the nodes can transmit the data at the same time. In a Half-Duplex mode, only one node can transmit the data at the same time.

Framing in Data Link Layer:

Framing is a point-to-point connection between two computers or devices consists of a wire in which data is transmitted as a stream of bits. However, these bits must be framed into discernible blocks of information. Framing is a function of the data link layer. It provides a way for a sender to transmit a set of bits that are meaningful to the receiver. Ethernet, token ring, frame relay, and other data link layer technologies have their own frame structures. Frames have headers that contain information such as error-checking codes.



Parts of a Frame:

A frame has the following parts –

- Frame Header – It contains the source and the destination addresses of the frame.
- Payload field – It contains the message to be delivered.
- Trailer – It contains the error detection and error correction bits.
- Flag – It marks the beginning and end of the frame.





Types:

1. Byte-oriented framing:

Computer data is normally stored as alphanumeric characters that are encoded with a combination of 8 bits (1 byte). This type of framing differentiates one byte from another. It is an older style of framing that was used in the terminal/mainframe environment

2. Bit-oriented framing:

This type of framing allows the sender to transmit a long string of bits at one time. IBM's SDLC (Synchronous Data Link Control) and HDLC (High-level Data Link Control) are examples of bit-oriented protocols. Most LANs use bit-oriented framing. There is usually a maximum frame size. For example, Ethernet has a maximum frame size of 1,526 bytes. The beginning and end of a frame is signaled with a special bit sequence (01111110 for HDLC). If no data is being transmitted, this same sequence is continuously transmitted so the end systems remain synchronized.

3. Clock-based framing:

In a clock-based system, a series of repetitive pulses are used to maintain a constant bit rate and keep the digital bits aligned in the data stream. SONET (Synchronous Optical Network) is a synchronous system in which all the clocks in the network are synchronized back to a master clock reference. SONET frames are then positioned within the clocked stream.



SNS COLLEGE OF TECHNOLOGY, COIMBATORE –35
(An Autonomous Institution)
DEPARTMENT OF AIML

